

PNEUMATIC STEEL STRAPPING TOOL WITH SEAL JOINT



TECHNICAL SPECIFICATIONS

DIMENSIONS

Length	430mm • 16.9"
Width	260mm • 10.2"
Height	310mm • 12.2"
Weight	11.3 kgs • 22.6lbs

FEEDING

Pressure range	5.5 -7 bar / 78 -99 psi
Air consumption	12 L/s - 25 cuft/min

PERFORMANCE

Max. tension force	9000 N 6 bar - 87 psi
Tensioning speed	6mt/m
Sealing	Seal double notches
Joint strength	80% of breaking strength*
Gear ratio	-

* variable according to strap type

MODEL

CODE	TYPE	STRAP	THICKNESS
T621943	ITA 62-19mm-9000N- 2B	R 850N/mm ₂	0.6mm 0.024" - 1mm 0.039"
		R 1100N/mm ₂	0.63mm 0.025" - 0.8mm 0.031"
T622543	ITA 62-25mm-9000N- 2B	R 850N/mm ₂	0.6mm 0.024" - 1mm 0.039"
		R 1100N/mm ₂	0.63mm 0.025" - 0.8mm 0.031"
T623243	ITA 62-32mm-9000N- 2B	R 850N/mm ₂	0.6mm 0.024" - 1mm 0.039"
		R 1100N/mm ₂	0.63mm 0.025" - 0.8mm 0.031"

SEAL DOUBLE NOTCHES



Pakmak Ambalaj Paketleme Makineleri
 10016 Sk. No.6 AOSB Çiğli / İzmir
 0 232 328 10 51
 info@pakmak.com

